



PLANILLA DE DOBLADO DE HIERROS

Pos.	Ubicación	diam. (mm)	sep. (cm)	long. (m)	cantid.	long. Total (m)	peso (kg)	Doblado
1	losa levantados (EXTREMAS O SIMPLE)	16	35,0	4,32	42	181,61	286,49	
2	losa rectos (EXTREMAS O SIMPLES)	16	35,0	4,26	42	178,92	282,25	
	repartición losa principal	8	20,0	7,36	44	323,84	127,72	
3	tabiques estribos	8	20,0	3,27	54	176,58	69,64	
4	tabiques estribos	8	20,0	3,59	54	193,86	76,46	
3 m	tabiques estribos (hierros 3 en long. m)	8	20,0	3,27	26	85,02	33,53	
4 m	tabiques estribos (hierros 4 en long. m)	8	20,0	3,59	26	93,34	36,81	

PLANILLA DE DOBLADO DE HIERROS

Pos.	Ubicación	diam. (mm)	sep. (cm)	long. (m)	cantid.	long. Total (m)	peso (kg)	Doblado
	Repartición en estribos	8	20	7,76	64	496,64	195,87	
5	zapata estribos inferiores	8	20,0	0,76	80	60,80	23,98	
6	zapata estribos superiores	8	20,0	0,92	80	73,60	29,03	
	repartición zapata estribos	8		7,76	16	124,16	48,97	
11	armaduras y refuerzos de alas	8	36,0	2,53	36	91,08	35,92	
12	armaduras y refuerzos de alas	8	36,0	2,00	32	64,00	25,24	
13	armaduras y refuerzos de alas	8	36,0	2,45	32	78,40	30,92	
14	armaduras y refuerzos de alas	8	36,0	9,01	18	162,18	63,96	

PLANILLA DE DOBLADO DE HIERROS

Pos.	Ubicación	diam. (mm)	sep. (cm)	long. (m)	cantid.	long. Total (m)	peso (kg)	Doblado
15	armadura guardarueda	8	20,0	1,36	44	60,02	23,67	
16	percha en guardarueda	8		4,26	4	17,04	6,72	
21	pasadores entre losas y estribos	10	15,0	0,25	98	24,50	15,10	
	repartición en alas (longitud promedio)	8	20,0	2,77	68	188,36	74,29	